




## MEET THE GARDEN TRACTOR THAT TAKES A BEATING – WITHOUT RETURNING THE FAVOR.

The Cub Cadet Series 2000 works hard for those who demand more out of their equipment. You get more power from professional-grade Kohler® Command® engines. More control and comfort available from electronic power steering (on GTX 2100 models), an adjustable steering wheel and a great seat. You even get more life out of your tractor with a fully welded steel frame, cast-iron transmission, cast-iron front axle and the legendary Cub Cadet direct shaft drive.

INNOVATIVE FEATURES FOR AN INCREDIBLE EXPERIENCE. THAT'S THE

**CUB CADET ADVANTAGE.**



### BETTER DRIVE SYSTEM

Direct shaft drive gives the Series 2000 the most efficient power transfer with no belts to slip or break. The dual pedal foot-controlled hydrostatic transmission gives you maximum power to handle attachments and is the ultimate in durability and performance.



### ELECTRONIC POWER STEERING (EPS)

With electronic power steering and electric deck lift on select models, you'll be rewarded with nearly effortless operation and smooth control. With EPS, you can let the tractor do the hard work for you (on GTX 2100 models).



### COMFORTABLE FEATURES

An adjustable tilt steering column, soft-touch steering wheel, high-back adjustable seat with armrests mean that you will stay comfortable while you mow. The ergonomic dash-mounted fingertip controls put the PTO, cruise and parking brake all within easy reach.

### FEATURES

42" TWIN-BLADE DECK  
AND 48", 50", 54"  
TRIPLE-BLADE DECKS

STAMPED OR FABRICATED  
DECK OPTIONS  
AVAILABLE

DIRECT SHAFT DRIVE

ELECTRONIC POWER  
STEERING (EPS)  
(on GTX 2100 models)

ELECTRIC DECK LIFT  
(on GTX 2100 models)

DUAL PEDAL  
FOOT-CONTROLLED  
HYDROSTATIC  
TRANSMISSION

CAST-IRON SERVICEABLE  
TRANSMISSION

SMARTJET™ DECK WASH

4- & 5-YEAR LIMITED  
WARRANTY†

ENGINE	GT 2000	GTX 2100
Engine type	20 HP* Kohler® Command® V-Twin OHV	23 HP* Kohler® Command® V-Twin OHV
Cylinders/material	2/cast-iron sleeve	
Lubrication	Fully pressurized automotive-style oil pump w/spin-on oil filter	
<b>DRIVE SYSTEM</b>		
Drive system	Direct shaft drive, foot-controlled hydro w/cruise control.	
Engine to transmission	Transmission: heavy-duty cast-iron housing w/BDU-10 hydrostatic pump and spin-on oil filter	
Cruise control	Heavy-duty shaft drive — 5-year limited warranty, no belts to stretch, slip or replace	
Rear wheel	Standard	
Transmission housing	Steel wheels with 4-bolt automotive-style lug nut mounting	
	Heavy-duty cast-iron	
<b>STEERING</b>		
Steering	Manual, 18" turning radius, cast-iron rack and pinion housing	Electronic Power Steering (EPS), tilt wheel w/18" turning radius, cast-iron rack and pinion housing
Front axle	Heavy-duty cast-iron w/dual grease fittings — 5-year limited warranty	
Spindles	3/4"	
Ball joints	4 automotive-style	
Rear axle diameter	1" diameter with dual steel drive hub	
Turning radius	18"	
<b>CHASSIS</b>		
Chassis/frame type	Fully robotically welded twin C-channel frame assembly/5-year limited warranty	
Hood & grill	Fully enclosed engine compartment	
Fender & bumper	Steel underflanged fender and heavy-duty steel bumper	
<b>ELECTRICAL SYSTEM</b>		
Alternator	15 amp. regulated	25 amp. regulated
Battery	12V/heavy-duty 275 cold crank amp.	
Charging system	Flywheel alternator	
Headlights	Standard	
System monitor package	Digital hour meter, change oil service minder, oil pressure indicator, battery voltage monitor, park brake and PTO start sequence LEDs	
Safety systems	Neutral start, operator presence, brake pedal lock, RevTEK™ reverse mowing technology	
<b>OPERATION</b>		
PTO clutch	Electronic fingertip engagement for smooth operation of deck or attachments	
Deck lift	Manual/10-position/spring-assisted deck lift	Electric lift w/height position
Brakes	Automotive-style disc	
Seat	Deluxe high-back seat with armrests and 6" travel	
<b>ADDITIONAL SPECIFICATIONS</b>		
Front tires	16" x 6.5"	
Rear tires	23" x 9.5"	
Forward speed	0 – 6.5 mph	
Reverse speed	0 – 3.5 mph	
Fuel tank capacity	4.5 gallon. Easy fill, large opening	
Engine oil capacity	2.0 qt.	
Transmission oil capacity	5.7 qt.	
Wheelbase	50.6"	
Overall length	76"	
<b>MOWER DECK</b>		
Deck type	42", 50", or 54" stamped – sold separately	42", 50", or 54" stamped or 48" and 54" fabricated sold separately
Cutting width/blades	42" twin, 50" or 54" heavy-duty triple blades	42" twin, 48", 50" and 54" heavy-duty triple blades
Deck cutting height	1.5" – 4.0"	
Deck drive system	Heavy-duty Kevlar® belt	
Anti-scalping	Greaseable anti-scalp wheels and front roller	
Deck spindles	Die-cast aluminum spindle housings and precision tapered roller bearings	
Deck pulleys	All steel w/heavy-duty bearings	
Deck wash	Patented SmartJet™ high-pressure deck washing system	
<b>WARRANTY†</b>		
	4-year/400-hr and 5-year/500-hr limited warranty	

This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating the machine, read, understand and follow all instructions in the manual and on the machine. Specifications and programs are subject to change without notice. Images may not reflect dealer inventory and/or unit specifications.

\* as rated by engine manufacturer

† See your local Cub Cadet Independent Dealer for warranty details.

773-04155 Printed in U.S.A. 12/10 © 2011 Cub Cadet

