

- Z-FORCE® S 46
- Z-FORCE® S 48
- Z-FORCE® S 54
- Z-FORCE® S 60
- Z-FORCE® S 48 LP
- Z-FORCE® S 60 LP

	Z-Force® S 48 LP	Z-Force® S 60 LP
ENGINE		
Engine type	726cc Liquid Propane-Powered Kawasaki® FR Series V-Twin	
Cylinders/material	2/cast-iron sleeve	
Engine start	Electric	
Lubrication	Fully pressurized automotive-style oil pump w/spin-on oil filter	
Engine oil capacity	2 qt.	
DRIVE SYSTEM		
Transmission	Dual EZT	Dual Hydro-Gear™ ZT-2800™ w/oil reservoir and filter
STEERING		
Steering	Steering wheel with tilt column	
CHASSIS		
Frame	1.5" x 3.0" box, fully welded steel	
Front axle	Fabricated steel	
Front wheel bearings	Steel	
ELECTRICAL SYSTEM		
Alternator	15 amp. regulated	
Battery	275 cold crank amp.	
Safety systems	Operator presence	
OPERATION		
PTO clutch	Electronic fingertip engagement	
Deck lift	Foot pedal	
Seat	High-back w/armrests and gel suspension	
Parking brake	Mechanical	
Hour meter	Standard electronic	
ADDITIONAL SPECIFICATIONS		
Forward speed	7 mph	8 mph
Reverse speed	4 mph	
Front tires	13" x 5.0" - 6"	
Rear tires	18" x 9.5" - 8"	20" x 10" - 8"
Turning radius	Zero	
Fuel tank capacity	33-lbs. liquid propane	
Cup holder w/utility bin	Standard	
Wheelbase	43"	
Overall length	70"	
Estimated weight w/deck	760 lbs.	805 lbs.
Rear tow hitch	Standard	
MOWER DECK		
Cutting width/blades	48" triple-blade, 3-in-1	60" triple-blade, 3-in-1
Greasable spindles	Standard	
Deck cutting height	1" - 4"	
Deck construction	11-gauge, floating, fabricated w/sloped nose	
Deck drive system	Belt driven, Kevlar®	
Anti-scalping	4 greasable gauge wheels	4 greasable gauge wheels and front roller
Deck wash	Patented SmartJet™ high-pressure deck washing system	
Accessories	Optional mulch kit/optional bagger/optional light kit	
Deck attach/removal	QuickAttach™ in seconds, no tools required	
WARRANTY*		
	3-year/180-hr limited warranty	



MEET THE REVOLUTIONARY ZERO-TURN WITH STEERING WHEEL CONTROL.


Now you have a choice: steering wheel or lap bars. The Z-Force® S features a steering wheel instead of lap bars, so it's easier to learn and use. And with Synchro Steer® technology, you get true zero-turn maneuverability and steering wheel control for greater stability on hills. All so you'll experience superior performance that makes your workday easier and your home more beautiful.

INNOVATIVE FEATURES FOR AN INCREDIBLE EXPERIENCE. THAT'S THE **CUB CADET ADVANTAGE.**



PREMIUM CUTTING DECK

Every inch of the Z Force® S's heavy-gauge, welded steel cutting deck has been engineered to make sure you get unsurpassed airflow, blade overlap, and quality of cut. Every time.



SYNCHRO STEER® TECHNOLOGY

Innovative Synchro Steer® technology, the steering wheel controls both the front wheels and the independently controlled back wheels for better control, better stability, better results. You'll be able to tackle tough terrain and steep hills quickly and easily with added traction and control — without damaging your yard.



A WIDER RANGE OF TERRAIN

Four-wheel directional zero-turn maneuverability, a low center of gravity and powerful engine allow you to navigate complex landscapes. Obstacles are no match for the Z-Force® S, which lets you glide over uneven ground and still cut a completely straight line across hills and slopes.

FEATURES

48", 54" OR 60"
FABRICATED DECKS
AND 46" STAMPED DECK

WEIGHT 655 LBS.
TO 805 LBS.

FOUR-WHEEL STEERING

ADJUSTABLE
STEERING COLUMN

DUAL HYDROSTATIC
TRANSMISSION

HEAVY-DUTY
PROFESSIONAL-GRADE
CUTTING DECK

SMARTJET™ DECK WASH

FULL LINE OF
ATTACHMENTS
AND ACCESSORIES
AVAILABLE

LIQUID PROPANE -
POWERED
MODELS AVAILABLE

3-YEAR LIMITED
WARRANTY†

†See specifications for warranty information.

This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating the machine, read, understand and follow all instructions in the manual and on the machine. Specifications and programs are subject to change without notice. Images may not reflect dealer inventory and/or unit specifications.



*as rated by engine manufacturer † See your local Cub Cadet Independent Dealer for warranty details.

ENGINE	Z-Force® S 46	Z-Force® S 48
Engine type	20 HP* Kohler® Courage® V-Twin	22 HP* Kohler® Courage® V-Twin
Cylinders/material	2/cast-iron sleeve	
Engine start	Electric	
Lubrication	Fully pressurized automotive-style oil pump w/spin-on oil filter	
Engine oil capacity	2 qt.	
DRIVE SYSTEM		
Transmission	Dual EZT	
STEERING		
Steering	Steering wheel with tilt column	
CHASSIS		
Frame	1.5" x 3.0" box, fully welded steel	
Front axle	Fabricated steel	
Front wheel bearings	Steel	
ELECTRICAL SYSTEM		
Alternator	15 amp. regulated	
Battery	275 cold crank amp.	
Safety systems	Operator presence	
OPERATION		
PTO clutch	Electronic fingertip engagement	
Deck lift	Foot pedal	
Seat	High-back w/armrests and gel suspension	
Parking brake	Mechanical	
Hour meter	Standard electronic	
ADDITIONAL SPECIFICATIONS		
Forward speed	7 mph	
Reverse speed	4 mph	
Front tires	13" x 5.0" - 6"	
Rear tires	18" x 9.5" - 8"	
Turning radius	Zero	
Fuel tank capacity	4.5 gal.	
Cup holder w/utility bin	Standard	
Wheelbase	43"	
Overall length	70"	
Estimated weight w/deck	655 lbs.	690 lbs.
Rear tow hitch	Standard	
MOWER DECK		
Cutting width/blades	46" twin-blade, 3-in-1	48" triple-blade, 3-in-1
Greasable spindles	Standard	
Deck cutting height	1" - 4"	
Deck construction	12 gauge, heavy-duty	11-gauge, floating, fabricated w/sloped nose
Deck drive system	Belt driven, Kevlar®	
Anti-scalping	4 greasable gauge wheels	
Deck wash	Patented SmartJet™ high-pressure deck washing system	
Accessories	Optional mulch kit/optional bagger/optional light kit	
Deck attach/removal	QuickAttach™ in seconds, no tools required	
WARRANTY†		
	3-year/180-hr limited warranty	

ENGINE	Z-Force® S 54	Z-Force® S 60
Engine type	24 HP* Kohler® Courage® V-Twin	26 HP* Kohler® Courage® V-Twin
Cylinders/material	2/cast-iron sleeve	
Engine start	Electric	
Lubrication	Fully pressurized automotive-style oil pump w/spin-on oil filter	
Engine oil capacity	2 qt.	
DRIVE SYSTEM		
Transmission	Dual Hydro-Gear™ ZT-2800™ w/oil reservoir and filter	
STEERING		
Steering	Steering wheel with tilt column	
CHASSIS		
Frame	1.5" x 3.0" box, fully welded steel	
Front axle	Fabricated steel	
Front wheel bearings	Steel	
ELECTRICAL SYSTEM		
Alternator	15 amp. regulated	
Battery	275 cold crank amp.	
Safety systems	Operator presence	
OPERATION		
PTO clutch	Electronic fingertip engagement	
Deck lift	Foot pedal	
Seat	High-back w/armrests and gel suspension	
Parking brake	Mechanical	
Hour meter	Standard electronic	
ADDITIONAL SPECIFICATIONS		
Forward speed	8 mph	
Reverse speed	4 mph	
Front tires	13" x 5.0" - 6"	
Rear tires	20" x 10" - 8"	
Turning radius	Zero	
Fuel tank capacity	4.5 gal.	
Cup holder w/utility bin	Standard	
Wheelbase	43"	
Overall length	70"	
Estimated weight w/deck	775 lbs.	790 lbs.
Rear tow hitch	Standard	
MOWER DECK		
Cutting width/blades	54" triple-blade, 3-in-1	60" triple-blade, 3-in-1
Greasable spindles	Standard	
Deck cutting height	1" - 4"	
Deck construction	11-gauge, floating, fabricated w/sloped nose	
Deck drive system	Belt driven, Kevlar®	
Anti-scalping	4 greasable gauge wheels and front roller	
Deck wash	Patented SmartJet™ high-pressure deck washing system	
Accessories	Optional mulch kit/optional bagger/optional light kit	
Deck attach/removal	QuickAttach™ in seconds, no tools required	
WARRANTY†		
	3-year/180-hr limited warranty	