


ZTT 42
ZTT 50



THE WORLD'S MOST MANEUVERABLE LAWN TRACTOR.


Only available from Cub Cadet, the innovative iSeries Zero-Turn Tractor gives you the attachment capability of a traditional tractor and the time-saving benefits of a zero-turn rider. Which means you can get done fast and get on with life. Plus, the award-winning ZTT is the only tractor engineered and built to take on hills with ease. After all, the world isn't flat. And neither is your yard.

INNOVATIVE FEATURES FOR AN INCREDIBLE EXPERIENCE. THAT'S THE **CUB CADET ADVANTAGE.**



TIGHTER TURNING

The world's first and only zero-turn lawn tractor features a steerable pivoting front axle, which allows you to make extremely tight turns. You can easily maneuver around any obstacles to reduce your trim time and finish faster.



BETTER TRACTION

A wide track and a low center of gravity provide extra traction and stability to mow a straight line on hills and inclines.



WIDER RANGE OF ATTACHMENTS

Optional front and rear attachments give you year-round performance for the ultimate in versatility.

FEATURES

42" TWIN-BLADE AND
50" TRIPLE-BLADE DECKS

WEIGHT 535 LBS.
TO 590 LBS.

SPRING-LOADED,
SINGLE-LEVER DECK LIFT

DUAL TRANSMISSION

PADDED FOOT RESTS

WIDE-TRACK FRONT AXLE

EXCLUSIVE KOHLER®
COURAGE® OHV ENGINES

HIGH-BACK SEAT

SMARTJET™ DECK WASH

FULL LINE OF
ATTACHMENTS AND
ACCESSORIES

3- AND 5-YEAR LIMITED
WARRANTY†

LOCATE A DEALER AT
CUBCADET.COM

YOUR INDEPENDENT DEALER CAN ANSWER ALL YOUR QUESTIONS
ABOUT THE MANY BENEFITS OF OWNING A CUB CADET.

†See specifications for warranty information.

cubcadet.com

ENGINE	ZTT 42	ZTT 50
Engine type	18 HP* Kohler® Courage® OHV single-cylinder	25 HP* Kohler® Courage® OHV twin-cylinder
Cylinders/material	1/cast-iron sleeve	2/cast-iron sleeve
Lubrication	Fully pressurized automotive-style oil pump w/spin-on oil filter	
DRIVE SYSTEM		
Drive system	Dual Hydro-Gear™ EZT	
Engine to transmission	Heavy-duty belt	
Rear wheel	4-bolt automotive-style lug nut mounting	
Transmission housing	Die-cast aluminum	
STEERING		
Steering	Variable pitch dual gear, dual drag links w/tie rod	
Front axle	Pivoting cast-iron w/4 grease fittings	
Spindles	3/4" w/grease fittings	
Ball joints	6 automotive-style	
Rear axle diameter	1" diameter with dual steel wheel drive hubs	
Turning radius	Zero-turning radius	
CHASSIS		
Chassis type	Robotically welded steel frame assembly	
Frame	Heavy-duty 12-gauge steel	
Hood & grill	Corrosion- and dent-resistant high-impact polymer	
Fender & bumper	Steel fender with high-impact pod overlay	Steel fender with high-impact pod overlay & tubular steel bumper
ELECTRICAL SYSTEM		
Alternator	15 amp. regulated	
Battery	12V/heavy-duty 190 cold crank amp.	12V/heavy-duty 235 cold crank amp.
Charging system	Flywheel alternator	
Headlights	Standard	
System monitor package	Digital hour meter, change oil service minder, battery voltage monitor, park brake and PTO start sequence LEDs	
Safety systems	Neutral start, operator presence, reverse safety switch, brake pedal lock, RevTEK™ reverse mowing technology	
OPERATION		
PTO clutch	Electronic fingertip engagement	
Deck lift	Manual/6-position/spring-assisted	
Brakes	2 automotive-style disc	
Seat	High-back seat, multiple-position fingertip adjustment mechanism	
ADDITIONAL SPECIFICATIONS		
Front tires	15" x 5"	15" x 6"
Rear tires	20" x 8"	
Forward speed	0 - 6.0 mph	
Reverse speed	0 - 3.2 mph	
Fuel tank capacity	2.8 gal. easy fill, large opening, rustproof	
Engine oil capacity	1.6 qt.	
Wheelbase	47.5"	
Overall length	69"	
Estimated weight w/deck	535 lbs.	590 lbs.
MOWER DECK		
Cutting width/blades	42" heavy-duty twin blades	50" heavy-duty triple blades
Deck cutting height	1.25" - 3.75"	
Deck construction	12-gauge steel	
Deck drive system	Heavy-duty belt	
Anti-scalping	2 wheels	2 wheels plus triple rear rollers for striping
Mulch kit	Optional	Standard
Deck spindles	Die-cast aluminum spindle housings w/sealed ball bearings	
Deck pulleys	All steel w/heavy-duty bearings	
Deck attach/removal	QuickAttach™ in seconds, no tools required	
Deck wash	Patented SmartJet™ high-pressure deck washing system	
WARRANTY†		
	3-year/120-hr and 5-year/500-hr limited warranty	



†Cub Cadet will provide a limited warranty for a period of 5 years or 500 hours, whichever occurs first, for the frame and pivoting cast-iron front axle on all new Cub Cadet iSeries ZTT Tractors. For complete details on 3-year and 5-year limited warranties, see your Cub Cadet Independent Dealer or operator's manual. 3 years or 120 hours, whichever comes first. Warranty does not cover normal wear on parts, batteries, and frame and front axle. Frame and front axle are covered for 5 years or 500 hours, whichever comes first. See operator's manual for details on Cub Cadet's Manufacturer's Limited Warranty for iSeries ZTT Tractors.

This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating the machine, read, understand and follow all instructions in the manual and on the machine. Specifications and programs are subject to change without notice. Images may not reflect dealer inventory and/or unit specifications.

*as rated by engine manufacturer †See your local Cub Cadet Independent Dealer for warranty details.

773-04157 Printed in U.S.A. 12/10 © 2011 Cub Cadet

